



# VLXS SERIES LOW RISE PAD LIFTS

7,000 - 10,000 lbs. / QUICK SERVICE LIFTS



MODEL SHOWN:  
VLXS10000BL



MODEL SHOWN:  
VLXS7000BL

## VLXS10 / VLXS7

### FIXED PAD / QUICK SERVICE LIFTS Increasing Productivity with Rotary Lift

The VLXS low-rise lift is your solution for quick service operation on today's passenger cars and trucks up to 10,000 lbs. Tire and brake work can now be performed on a wider variety of vehicles, thanks to the lift's pads, adapters, wider drive-over capability. The vehicle spotting combinations allow lifting of uni-body and frame engagement — reaching recommended manufacturers pick-up points on most vehicles on the road today.

#### FEATURES:

- 10,000 and 7,000 lbs. capacity models
- Dual lifting cylinders
- Non-slip deck padding provides surface for adapters or vehicle pick-up points
- Ramps and side drive-over areas accommodate wider wheelbases
- ALI Gold Certified




#### VLXS10 3-Position Adapters

Rubber contact pads on three sides increase the positioning capabilities.



Lo: 4 5/16" Mid: 6 5/16" High: 8 9/16"

The VLXS10 also comes with a set of four 1 1/2" rubber block adapters for low-profile vehicles.



#### VLXS7 Rubber Block Adapters

Standard with a set of four (4) each rubber blocks for quick access to lower profile and unibody frame vehicles. Blocks are 1 1/2" and 3" in height.



MODEL  
Lift Colors are Blue and Red

VLXS7/10  
PAD LIFTS

SURFACE MOUNT	VLXS7000 VLXS10000
<b>Lift Capacity</b>	7,000 lbs. 10,000 lbs.
<b>Rise*</b>	21 3/4" Flat Rise 23 1/4" Short Pad 26 1/4" Low Step 28 1/16" Mid Step 30 5/16" High Step / Tall Pad
<b>Width Overall</b>	78 1/2"
<b>Width Between Platforms</b>	22 3/4"
<b>Length Overall</b>	90 1/2"
<b>Length of Platform</b>	51 1/4"
<b>Length of Pad</b>	17"
<b>Outside Width of Platforms</b>	70 3/4"
<b>Lowered Height</b>	4"
<b>Horizontal Movement</b>	16" During Rise
<b>Locking Leg Heights</b>	13 3/8" / 17 3/8" / 21 3/8"
<b>Single Voltage Phase</b>	115v
<b>Time of Full Rise</b>	40 seconds

\*Rise measures floor to top of supplied adapters at full stroke. Surface mounted measurement.

#### Rotary Lift

2700 Lanier Drive / Madison, IN 47250, USA

rotarylif.com     

#### North / South America Information

Sales: 800.640.5438  
userlink@rotarylif.com

Tech. Support: 800.445.5438  
techlink@rotarylif.com

#### Global Contact Information

USA: 1.812.273.1622  
Canada: 1.905.812.9920  
Latin America / Caribbean: 1.812.273.1622  
Brazil: +55.11.4534.1995

Government Sales: 800.445.5438 X5655

For additional information: rotarylif.com/Government-Purchasing-Assistance/

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.

Lit# Rotary VLXS SERIES Cutsheet.2019.11

©2019 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.