



SMO14N101YBL

# LIFT QOR



SPOA10N700BL

## Quoting a Lift

### Minimum Ceiling Height

- 2-Post - 10,000 lb. 12'
- 2 Post -10,000 lb. SHOCKWAVE, 12' 6"
- 2-Post - 12-15,000 lb. 14'8"
- 2-Post 16-20,000 lb. 15' 2"
- 4-Post - 14,000 lb. (76" + tallest vehicle)
- Scissor 14,000 lb. (72" + tallest vehicle)

### Minimum Bay Size

- 2-Post - 10,000 lb. 12' x 24'
- 2-Post – 12,000 lb. 12' x 26'
- 2-Post 15-20,000 lb. 15' x 30'
- 4-Post - 14,000 lb. 12' x 24'
- Scissor – 14,000 lb. 14' x 27'

### Concrete Requirement 3000 PSI

All models above require 4.25" min. concrete depth  
In good condition without cracks or seams within 6" of  
each anchor

### Possible Accessories to Quote

- Additional Adapters
- Rolling Bridge Jacks
- Air Line Kit



## Ordering a Lift


Send orders to  
orders@vsgdover.com

Specify Color of Lift  
BL – Blue / RD – Red

### Complete Ship to Information

- Business Name
- Address
- Contacts Name

Phone # to Call before Delivery

Confirmation that a Forklift will  
be on Site upon delivery 



## Receiving a Lift

Forklift Must be On Site with a  
5,000-lb. minimum lifting Capacity



Inspect all product BEFORE  
Signing Delivery Receipt

Check to confirm that the  
product being delivered is what  
was ordered.

Document any **damage** on the  
Delivery Receipt. 

Take photos of any damage  
before unloading.

Notify Rotary/Forward Immediately  
of any Damage or Issues with your  
order.  
**(800) 445-5438**

**\*\*\*It is the responsibility of the consignee to offload the lift\*\*\***